



# QMFZ2.E214138 - Plastics - Component

## Plastics - Component

See General Information for Plastics - Component

**PR COMPOUND S R L**  
 VIA UGO FOSCOLO 3/C  
 20060 BASIANO, MI ITALY

E214138

Material Dsg	Color	Min. Thk mm	Flame Class	H H		Elec	R T I		H D		
				W	A		Mech	Imp	Str	V	4
				I	I				R	5	I
<b>Polyamide 6 (PA6), "Newnil", furnished as pellets.</b>											
<b>B 2430</b>	ALL	1.5	HB	-	-	65	65	65	-	-	-
		3.0	HB	-	-	65	65	65			
<b>B 2460(f1)</b>	BK	1.5	HB	-	-	65	65	65	-	-	-
<b>B 2460(f2)</b>	ALL	1.5	HB	-	-	65	65	65	-	-	-

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2017-07-18

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"