UL Product iQ™



QMFZ8.E214138 - Plastics Certified for Canada - Component

Plastics Certified for Canada - Component

See General Information for Plastics Certified for Canada - Component

Min.

PR COMPOUND S R L

E214138

C

RTI

VIA UGO FOSCOLO 3/C 20060 BASIANO, MI ITALY

				• •	•••	•				•
		Thk	Flame	W	Α	V	Elec	Mech		T
Mtl Dsg	Color	mm	Class	1	l	Α		Imp	Str	I
Polyamide 6 (PA6), "Newnil", furnished as pellets.										
B 2430	ALL	1.5	t		-	. - 1	65	65	65	-
		3.0	НВ			-	65	65	65	
B 2460(f1)	вк	1.5		-	-		65	65	65	-
B 2460(f2)	ALL	1.5	-			-	65	65	65	-

⁽f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

Marking: Company name, material designation, Recognized Component Mark for Canada, generic polymer identification, color number where appropriate and batch or lot number or date of manufacture on container, wrapper or molded on finished part.

Last Updated on 2017-07-18

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

⁽f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.